

HOLZ BIO

EFFICIENT PRODUCT FOR PROTECTING AND IMPREGNATING WOOD.
A LONG-TERM PROTECTION AGAINST ROT, MOULD, WOOD PESTS ETC.

PURPOSES

Holz BIO provides intensive wood protection against rot, mould, wood pests and turning blue. The product is suitable for both internal and external conditions.

Holz BIO is used for protecting new or previously with wood preservative processed wood. The product is suitable for processing residential and communal premises, saunas, garden and outdoor furniture, greenhouses, cellars, flooring of firm grounds, logs, frames and shaved or sawed construction elements in contact with people or domestic animals and affected by active bio-destruction. The product can be used independently or as a primer.

Holz BIO is not for application on surfaces previously covered with drying oil, paint, varnish or other film-forming or water-repellent material.

MAIN ADVANTAGES

- ✓ According to EN 84, Holz BIO protects wood against *Coniophora puteana*, *Gloeophyllum trabeum* and *Coriolus versicolor*.
- ✓ Combines chemically with wood without changing its texture or preventing air circulation.
- ✓ Protects wood from rotting, mould, turning blue, timber-worms and other biological decomposers.
- ✓ Stops even already begun bio-destruction.
- ✓ Wood remains durable and recoatable.
- ✓ Forms a 3-level bio-protection in wood and increases wear resistance.
- ✓ Ecologically safe, non-toxic, non-carcinogenic.
- ✓ Fire and explosion proof.

DIRECTIONS FOR USE

Before applying Holz BIO, always clean the surface of all dust, bark or other contaminants. Holz BIO may be applied with a brush, roller or by immersing at the temperature above +5⁰C (with humidity under 75%).

Apply 2–3 coats with an interval of 40–60 minutes with normalized total consumption being 200–300 g/m² (1 l on 3–5 m²). Each freshly applied coat should be dried at air temperature of +12⁰C to +40⁰C (with humidity under 75%).

You can paint or cover the surface with other decorative materials after 24–72 hours. Climate conditions like low temperatures and/or high relative humidity can lengthen the drying time. The product is completely combined with wood in 7 days.

Do not process frozen wood! Do not mix Holz BIO with other products!

Stir thoroughly before applying! (Bottom sediment doesn't affect the quality of the product)

SAFETY MEASURES

Keep locked up and out of the reach of children. Wear suitable protective clothing, gloves and eye/face protection. In case of contact with eyes or mouth, rinse immediately. If you feel unwell seek medical advice. Use only in well-ventilated areas. Discard with other household waste products.

COMPOSITION

0,2% DDAC substance, biocide reg. number: 0426/08, ferric(III)hydrophosphate, water and additives.

STORAGE AND TRANSPORTATION

Store and transport Holz BIO in hermetically sealed original containers separately from food products. Keep at temperature above -5⁰C. The storing period of the product is 24 months.